



Přístroj c.

Výpocet tlumice (požadavek k Lw)

DIMsilencer 6.0

Upozornění	Prodejce	Zákazník
	/	/

Název produktu	Oznacit	[] Prutok	[] Pokles tlaku	Lw pred Tlumic [dB]								Lw po dB(A)
				63	125	250	500	1k	2k	4k	8k	
BDLD 935 855 150 150 30 09	Tlumic Přívod 1	1583	max 20 11	Přívod, BDLD 935 855 150 2000 30 09								max 0 58
				68	75	73	74	69	68	67	58	76
SLRS 200 50 1000 855 1000	Tlumic Přívod 2	500	max 20 6	Přívod, BDLD 935 855 150 150 30 09								max 0 37
				64	63	53	55	51	50	48	38	58
BDLD 935 855 1450 150 30 09	Tlumic Výfuk 1	1583	max 20 14	Výfuk, BDLD 935 855 1450 150 30 09								max 0 55
				65	70	78	77	80	80	82	80	87
BDLD 855 935 150 150 30 07	Tlumic Výfuk2	1583	max 20 7	Odvod, BDLD 935 855 1450 150 30 09								max 0 39
				60	53	45	37	34	42	51	51	55
SLRS 200 133 1000 900 2000	Tlumic Sání	1583	max 20 8	Sání, BDLD 935 855 2000 150 30 09								max 0 40
				63	68	58	57	57	52	53	42	62
BDLD 1000 900 1200 150 30 09	Tlumic Odvod	1583	max 20 9	Odvod, SLRS 200 133 1000 900 2000								max 0 35
				57	61	60	60	56	54	56	54	63



Přístroj c.

Výpocet tlumice (požadavek k Lw)

DIMSilencer 6.0

Upozornění	Prodejce	Zákazník
	/	/

Název produktu	Oznacit	[] Prutok	[] Pokles tlaku	Lw pred Tlumic [dB]								Lw po dB(A)
				63	125	250	500	1k	2k	4k	8k	
BDLD 855 1240 150 150 30 07	Tlumic Přívod 1	1931	max 20 3	Přívod, 64 73 75 74 70 72 70 64 78								max 0 62
SLRS 200 110 1240 630 1000	Tlumic odvod 1	1930	max 20 9	Odvod, SLRS 200 110 1240 630 1500 59 67 60 59 56 57 56 50 64								max 0 46
SLRS 200 110 1240 630 500	Tlumic odvod 2	1930	max 20 5	Odvod, SLRS 200 110 1240 630 1000 56 59 43 34 25 30 39 38 46								max 0 40
SLRS 200 85 855 1240 1000	Tlumic Přívod 2	1931	max 20 19	Přívod, BDLD 855 1240 150 150 30 07 61 63 58 58 54 56 53 47 62								max 0 41
SLRS 200 110 1240 855 1850	Tlumic sání	1930	max 20 7	Odvod, SLRS 200 85 855 1240 1000 59 67 60 59 56 57 56 50 64								max 0 39
BDLD 1240 855 150 1350 30 10	Tlumic Výfuk 1	1930	max 20 5	Výfuk, SLRS 200 110 1240 855 1850 66 73 77 78 79 82 80 76 87								max 0 53
SLRS 200 110 1240 855 1000	Tlumic výfuk 2	1930	max 20 5	Výfuk, BDLD 1240 855 150 1350 30 10 59 54 44 40 37 46 49 47 53								max 0 38



Přístroj c.

Výpocet tlumice (požadavek k Lw)

DIMsilencer 6.0

Upozornění	Prodejce	Zákazník
	/	/

Název produktu	Oznacit	[] Prutok	[] Pokles tlaku	Lw pred Tlumic [dB]								Lw po dB(A)
				63	125	250	500	1k	2k	4k	8k	
BDLD 450 630 150 1000 30 06	Tlumic odťah 1	500	max 20 11	Prívod, 76 73 70 65 65 62 62 55 70								max 0 51
SLRS 200 50 750 750 1500	Tlumic odťah 2	500	max 20 18	Odvod, BDLD 450 630 150 1000 30 06 74 63 46 35 30 34 40 34 51								max 0 40
SLRS 200 50 1000 600 1500	Tlumic Prívod	500	max 20 16	Prívod, SLRS 200 50 750 750 1500 70 70 74 70 64 63 58 54 72								max 0 39
BDLD 630 550 150 150 30 07	Tlumic sání 1	500	max 20 7	Sání, BDLD 630 450 150 150 30 07 72 68 56 55 53 46 47 40 59								max 0 47
SLRS 200 115 630 550 1500	Tlumic sání 2	500	max 20 7	Sání, BDLD 630 550 150 150 30 07 70 59 37 36 35 30 31 22 47								max 0 40
BDLD 630 450 150 150 30 07	Tlumic výfuk1	500	max 20 11	Výfuk, SLRS 200 115 630 550 1500 66 62 59 61 60 55 51 49 64								max 0 47
SLRS 200 115 630 450 500	Tlumic výfuk2	500	max 20 5	Výfuk, BDLD 630 450 150 150 30 07 64 53 40 42 42 39 35 31 47								max 0 39